

SWL R 1000

STANDARD EQUIPMENT



POWERED by HONDA™

Equipped with:

- Ideal for large surfaces • Large filter surface distributed on 6 cartridge filters fitted with electric filter shaker • Side brush raising control • **Complete right/left side brush** • Suction switch off
- Flashing light • Main brush pressure regulation • Indirect back collection • Front dust vacuum system
- Quick changing of the main brush and side brush without tools • Long life elastic belts • Suction selection lever • Antistatic device • Battery level indicator • Wide collector tank • Heavy duty steel frame
- Adjustable seat • Perfectly balanced weight of the components, thus resulting in totally safe quick changes of direction • Battery and battery charger not included. • Front light system (**optional on request**), standard for models code 0.061.0030 - 0.061.0039

- 0.961.0640
PP SWL R 1000 ET
- 0.961.0015
PP-Mixed steel SWL R 1000 ST

- 2 x 0.961.0007
PP SWL R 1000 ET
- 2 x 0.961.0023
PP-Mixed steel SWL R 1000 ST

- 6 x 0.961.0004
paper filter 14 µm

Optional:

- 0.961.0031 Anti-trace wheels
- 0.961.0024 polyester filter
- 0.961.0025 Hepa filter
 - 0.961.0029 Steel collector tank
 - 0.961.0030 Right brush protection
 - 0.961.0090 Left brush protection

Battery(model ET):

- 4 x 0.107.0004 tubular battery pb-acid 6V180Ah C5 + 3 x 5.511.0561 + 1x 5.511.1948
- 4 x 0.107.0072 GEL Battery 6 MFP 180-6V 180Ah C5 + 3 x 5.511.0561 + 1x 5.511.1948
- 4 x 0.107.0082 Battery - 6V 250Ah C5 + 3 x 5.511.0561 + 1x 5.511.1948

Battery charger (model ET):

- 0.108.0080 Battery charger 24V-30A 115-240V 50-60 Hz

Available models with limiting gradient 20%

SWL R 1000 ET cod. 0.061.0049

SWL R 1000 ET Light cod. 0.061.0050

SWL R 1000 ST cod. 0.061.0051

SWL R 1000 ST Light cod. 0.061.0052

	SWL R 1000 ET	SWL R 1000 ST	SWL R 1000 ET Light	SWL R 1000 ST Light
code	0.061.0006	0.061.0007	0.061.0030	0.061.0039
main brush width	700 mm / 27,56 inc	700 mm / 27,56 inc	700 mm / 27,56 inc	700 mm / 27,56 inc
main brush + 1 side brush	920 mm / 36,22 inc	920 mm / 36,22 inc	920 mm / 36,22 inc	920 mm / 36,22 inc
main brush + 2 side brushes	1150 mm / 45,28 inc	1150 mm / 45,28 inc	1150 mm / 45,28 inc	1150 mm / 45,28 inc
collector tank	62 lt / 16,3 gal	62 lt / 16,3 gal	62 lt / 16,3 gal	62 lt / 16,3 gal
max working capacity	6200 m ² /h-66736 ft ² /h	7700 m ² /h-82881 ft ² /h	6200 m ² /h-66736 ft ² /h	7700 m ² /h-82881 ft ² /h
traction / limiting gradient	rear wheels / 10%	front wheel / 10%	rear wheels / 10%	front wheel / 10%
max speed	5,8 km/h-3,60 mile/h	7,2 km/h-4,5 mile/h	5,8 km/h-3,60 mile/h	7,2 km/h-4,5 mile/h
motor type / power	24V / 1150W	Honda 5,5 HP / 4,1kW	24V / 1150W	Honda 5,5 HP / 4,1kW
filtering surface	6 m ² / 64,6 ft ²	6 m ² / 64,6 ft ²	6 m ² / 64,6 ft ²	6 m ² / 64,6 ft ²
filter shaker	electric	electric	electric	electric
dimension / weight	143x91x114cm/260kg	143x91x114cm/300kg	143x91x114cm/260kg	143x91x114cm/300kg