INDUSTRIAL

DTX100 1-26 SM Ex 2-22











Equipped with:

- 1 single stage side channel blower with three-phase induction motor
- AISI 304 non-magnetic stainless steel container (with side inlet channel) & filter chamber.
- Power coated steel structure.
- Mechanical horizontal & simple manual filter cleaning system
- Antistatic polyester non woven fabric pockets filter, class M
- Wheeled AISI 304 s.s. container with inbuilt quick release handle, drain plug and full load level
- Trolley with front pivoting non-marking wheels (with breake) & large inbuilt accessories basket
- Removable motors unit header through metal hooks

STANDARD EQUIPMENT

0.144.0117 Antistatic Polyester pockets filter 2 m², class M 0.144.0008 Quick release adaptor Ø 60-50 (1x)

0.144.0008 Quick release adaptor Ø 60-50 (1). There isn't any hose or tool provided within the unit.

Optional minimum set to run the unit:

6.205.0049 3 m complete EVA Ø 50 hose set (1x)

Optional:

Longopack set
0.144.0110 Hopper for spool bag collection
0.144.0111 Tray for spool bag collection
0.144.0112 Longopack 22m bag spools (box
of 4)

Filters

0.144.0118 Antistatic Polyester pockets filter 3m², class M

0.144.0119 180°C Heatproof polyester pockets filter 2m², class M

0.144.0120 Flat cartridge Hepa secondary filter assembly kit 0.144.0121 Flat cartridae Hepa filter

0.144.0121 Flat cartridge Hepa filter (replacement)

Wet operations

0.144.0045 Galvanized floater support (without floater)

0.144.0046 Floater for wet suction 0.144.0122 Wet filter protection cone for floater stop

0.144.0113 Container discharge faucet kit

Metal chips separations

0.144.0123 Galvanized chip basket including floater

0.144.0122 Wet filter protection cone for floater stop

	DTX100 1-26 SM Ex 2-22
code	0.045.0303
abs. power W	2600
n°/type motor	1/induction
max vacuum (actual)	32 kPa (26 kPa)
max Airflow	320 m³/h - 89 l/s
container capacity	100
noise level	78 dB(A)
voltage	400 V~50 Hz (3Ph)
inlet Ø - type (s=straight; t=tangential)	60 mm - t
filtering capacity/surface	2 μm - 99,9% (M Class)/ 20000 cm²
cable lenght	10 m
dimensions/weight	80x60x171 cm / 102kg - 225 lb