



Model T1 Specifications

CORD-ELECTRIC WALK-BEHIND SCRUBBER

| Feature | Specification |
|--|---|
| Scrubbing System | |
| Cleaning path | 15 in / 380 mm |
| Solution tank capacity | 3.0 gallon / 11.4 liter |
| Productivity (per hour) | |
| Theoretical Max | 15,920 ft ² / 1,480 m ² |
| Estimated Actual* | 8,690 ft ² / 810 m ² |
| Solution Flow Rate | 0.10 gpm / 0.38 lpm |
| Scrub Motors | 0.4 hp / 0.3 kW |
| Scrub Motor Speed | 2400 rpm |
| Brush down pressure | 33 lb / 15 kg |
| Brush size | 3.5 in / 89 mm |
| Recovery System | |
| Recovery tank capacity | 4.5 gallon / 17.0 liter (Includes demisting chamber) |
| Vacuum fan | |
| Motor | 1.2 hp / .88 kW |
| Stages | 2-stage |
| Water lift | 86 in / 2180 mm |
| Airflow | 99 cfm / 2.8 m ³ /min |
| Construction & Power System | |
| Chassis construction | Cast aluminum frame, rotational molded tanks and injection molded plastic cover |
| Power supply | 120V or 230V |
| Frequency | 50/60 Hz |
| Cable length | 50 ft / 15 m |
| Electrical Safety Approvals | ETL Tested for UL & CSA Standards |
| Dimensions / Weight / Sound level | |
| Length | |
| Handle in working position | 45.4 in / 1150 mm |
| Handle in folded position | 27.3 in / 690 mm |
| Width | |
| Base | 19.7 in / 500 mm |
| Squeegee | 17.5 in / 440 mm |
| Height | |
| Base (folded handle for storage) | 23.8 in / 600 mm |
| With handle up | 34 in / 860 mm |
| Net weight | 97 lb / 44 kg |
| Working weight (with water) | 121 lb / 55 kg |
| Sound level** (operator's ear) | 72 dBA |
| Warranty | 3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION. |

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA