


Comfort XXS IDS



STANDARD EQUIPMENT



Equipped with:

- **IDS: Integrated Disinfection System**
- 2 adjustable nozzles with adjustable flow rate
- Combined disinfection system connected directly to the solution tank suitable for sanitizing large surfaces
- 32 kg. of constant pressure on the brushes.
- Double counter rotating brush (66 cm of scrubbing width) obtaining better stability and constant pressure.
- Great working autonomy thanks to the possibility to use 4 batteries 6 V 240 Ah and to rear wheel-drive.
- Large load tank capacity (real load of 85 l.), resulting in reduced numbers of stops and maximum use of battery for effective operation of the machine.
- Ergonomic steering wheel of new design with user friendly controls and digital display.
- Easy access to electrical components.
- Inspection cover for fast and easy cleaning and sanification of dirt water tank.
- Automatic device that stops brushes and detergent water outflow when the machine is stationary.
- Self-levelling brush plate.
- **Automatic detergent dosing system.**
- It is possible to install IDS on standard machines if preset

* **New, standard on machines starting from 2022, compatible with all previous machine models**

Integrated Disinfection System



	Comfort XXS 66 IDS
code	8.579.0033
power supply	24V (batteries and battery charger included)
scrubbing/squeegee width	660/855 mm
max working capacity	3250 m ² /h
solution tank capacity	80 l/19.81 gal
recovery tank capacity	80-85 l/19.81-21.13 gal
traction	rear wheel-drive/400 W
RPM/pressure on the brushes	170/32 kg/70.54 lbs
brush motor power	2 X 400 W
max gradient empty/full tank	13%/10%
depression/vacuum motor	1300 mmH ₂ O/400 W
dimensions/weight	123x63x121 cm/217 kg

OPTIONAL



IDS: integrated sanitizing system:
Maximum operational flexibility:
the system allows sanitization
to be carried out before, during
and after the traditional surface
washing.
Separate function for chemical
dosage.
User friendly control panel.
Steering wheel with digital controls
and display

Squeegee and brush plate
mechanical and user friendly
lifting lever: min. maintenance
cost training time for the users.
Scrubbing unit with double brush
with brush plate made of steel for
a great pressure (32 Kg.) on the
floor resulting in an easy and deep
cleaning of any kind of dirt.



Rear wheel-drive on 2 wheels allows
the machine to get over remarkable
slopes . Detergent solution is
cleansed by an external completely
accessible filter, that holds any
impurities, thus protecting the
solenoid valve. The easy access to all
internal components of XXS make it
possible to reduce maintenance cost.
Detergent tank 2lt.

The comfortable and ergonomic
seat allows the operator to work
effortless for a long time, improving
productivity. Its very compact size
make it perfect to work in small
areas where walk behind models
are usually used. The use of XXS
makes working easier and quicker
with a huge saving of time.



- 4 x 0.107.0004
Tubular battery Pb-acid
6V 180Ah C20 + 2 x
5.511.0561 connection cable
batteries



- 4 x 0.107.0072
Gel battery 6 MFP 180
6V 180Ah C5 + 2 x
5.511.0561 connection cable
batteries



- 2 x 0.107.0002
Tubular battery Pb-acid
12V 118 Ah C5




- 0.108.0080
Battery Charger 24V 30A
220-240/50-6



- 4.508.1594 Polyurethane
front blade L.960 TH.3 Sh.40
- 4.508.1596 Polyurethane
rear blade L.1000 TH.4
Sh.40



- * • 2 x 5.511.2208
Tynex brush Ø 330 mm-13"
- 2 x 5.511.2209
PP 0,3 brush Ø 330 mm-13"
- 2 x 5.511.2210
PES brush Ø 330 mm - 13"



- * • 2 x 5.511.2211
EWU pad driver
Ø 330 mm-13"



- 6.508.0030 - Ø 340 mm -
13"- beige (5 pcs.)
- 6.508.0037 - Ø 340 mm -
13"- green (5 pcs.)
- 6.508.0044 - Ø 340 mm -
13"- black (5 pcs.)



- 6.505.0062
Flashing light