

Comfort L

LEVEL



STOP



Equipped with:

- Suitable for maintenance and deep cleaning of medium and large areas (up to 7.000 m²)
- More than 120-170 kg of constant pressure on the brushes
- 300 litres solution tank capacity allows exceptional autonomy and productivity
- Stability even when fully loaded
- Innovative traction system with three independent motor wheels controlled by electronic cards
- Easy access to electrical components Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic control system for brush rotation and detergent water outflow
- Antifoam device
- Self-levelling brushes, hour meter, solenoid valve. High-performance batteries resulting in high-working efficiency.
- Quick refilling system

*** New, standard on machines starting from 2022, compatible with all previous machine models**

STANDARD EQUIPMENT

*



- 3 x 5.511.2223
PP brush Ø 406 mm - 16"



- 4.508.0219
Front squeegee blade L.1500 mm
Shore 40 Th. 4 mm
- 4.508.0218
Rear squeegee blade L.1580 mm
Shore 33 Th. 6 mm

	Comfort L 122
code	8.572.0002
power supply	36V
scrubbing/squeegee width	1220/1450 mm
max working capacity	8540 m ² /h
solution tank capacity	280 l/73.97 gal
recovery tank capacity	315-340 l/83.2-89 gal
traction type/power	3-wheels drive/3 x 600 W
RPM/pressure on the brushes	150/170 kg/374 lbs
brush motor power	3 x 1000 W
max gradient empty/full tank	10%/8%
depression/vacuum motor	1800 mmH ₂ O/600 W
dimensions/weight	222x130x169 cm/607 kg

OPTIONAL



Designed to perform the hardest work and to resist even to extreme stresses with maximum comfort; the frame is made of steel profiles with a thickness varying from 5 to 12 mm, protected with a high resistance corrosion-proof paint.



• 0.107.0010
Battery box Pb-acid
36V 525 Ah C5

• 0.107.0013
Gel battery box
36V 400 Ah C5



• 0.108.0003
Battery Charger 24V/36V
50/60A - 220-240/50-60



• 4.508.1167 Polyurethane
front blade L.1500 TH. 4
• 4.508.0897 Polyurethane
rear blade L.1580 TH. 5

The unique anti foam device dramatically reduces the foam generation and prevents it from touching the suction motor, thus protecting its operation.
The electronic floating switch stops suction when the tank is full.
Large tank opening for fast and easy cleaning and sanification.



* • 3x 5.511.2224
Tynex brush Ø 406 mm-16"

• 3x 5.511.2225
PP 0,3 brush Ø 406 mm-16"

• 3x 5.511.2226
PES brush Ø 406 mm - 16"



* • 3x 5.511.2227
EWU pad driver Ø 406 mm-16"



• 6.508.0031 - Ø 406 mm - 16"- beige (5 pcs.)
• 6.508.0038 - Ø 406 mm - 16"- green (5 pcs.)
• 6.508.0045 - Ø 406 mm - 16"- black (5 pcs.)



The cleaning solution tank with an exceptional capacity of 300 liters and the high autonomy of the battery ensure a productivity at the top of the range. The wide rear opening allows for an easy and quick refilling of the cleaning solution tank.

The motorwheels, designed and built by LAVOR, grant optimal performances and exceptional reliability (over 30.000 hours). The innovative three-wheel drive system ensures perfect traction in every operating condition.
The high power of the three motorwheels allows the machine to get over remarkable slopes.

